

Data sheet

Commercial Art.No.: 99.906.0000.7

Distributor RST20i3B 3P1 F VG SW

RST20i3 compact distribution unit, 3 pole, application 250/400V, 20A, 1 input and 3 outputs, with fastening option, coding color black, color of housing black



Commercial Art.No.	99.906.0000.7
EAN	4015573971288
Order Unit	1

Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Lockable	self-locking (unlocking by tool)
Color of coding/ contact carrier	black
Color of separate housing (only for modular versions)	black
Color of separate adapter (if present)	black
Marking of poles	L, N, PE

Model

Number of inputs	1
Number of outputs	3
Type of fastening	yes
Degree of protection (IP)	IP66/68 (3m;2h) /IP69
Type of distributor	Compact distributor

Material

Housing material	Polyamide
halogen free	yes
Contact material	CuZn
Fire load	1.926 kWh
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	162 mm
Width	104 mm

Height	57.2 mm
--------	---------

Classification

ECLASS 11	
ECLASS 8.1	27440603
ETIM 7.0	EC002567
ETIM 6.0	EC002567
ETIM 5.0	EC002567
ETIM 4.0	EC002567

Product compliance

ROHS conformity status	Compliant/Exempted
ROHS exceptions	III-6(c)
REACH-SVHC conformity status	Duty-To-Declare
REACH-SVHC substances	Lead
REACH-SVHC CAS numbers	7439-92-1

Fits with

Commercial Art.No.:	Article-type description:	Description:
99.712.0000.7	Cable assembly RST20i3K1BF 15 15SW	RST20i3/2 mains connection cable RST20i3 female - male Schuko, 3 pole, assembled with shrinkage tube, application 250V, 16A, cable type H07RN-F, length 1.5m, cross section 1.5mm ² , coding color black