

## Data sheet

Commercial Art.No.: 78.002.4156.0

Modular insert MOD BUC 17 16



Commercial Art.No.	78.002.4156.0
EAN	4049088381812
Order Unit	10

Certificates / Approvals



## Technical data

### Classification

ECLASS 11	
ECLASS 8.1	27440205
ETIM 7.0	EC000438
ETIM 6.0	EC000438
ETIM 5.0	EC000438
ETIM 4.0	EC000438

### General

Model	Female insert
Inflammability class of insulation material acc. with UL94	V0
Color	Grey
Mating cycles	500
Pollution degree	2
Modular version	yes
Operating temperature range min.	-40 °C
Operating temperature range max.	120 °C

### Connection Data

Connection type	Crimp
Number of poles	17
Plus switching contacts	0
Number of pole for rated current 2	0
Number of pole for rated current 3	0
With wire protection	No
Protective contact	No

### Technical Data UL/CSA

Rated voltage according to UL/CSA	600 V
Rated current according UL	10 A
Rated current according CSA	10 A

**Model**

With housing	No
--------------	----

**Contacts**

Contact material	See contacts
Surface	Silver-plated
Contact resistance	$\leq 3$ mOhm
Wire strip length	8 mm

**Technical Data DIN EN 61984**

Nominal voltage	
Nominal current	10 A
Rated impulse voltage	2.5 kV

**Product compliance**

REACH-SVHC conformity status	Compliant
------------------------------	-----------