

Spring-cage connection terminal block-
UJ1-2.5/3RD - 021010



Spring-cage connection terminal block , rated voltage:/ , Max. operating current:/, connection method : Spring-cage connection , number of connections : 3 , crimping range : 0.2mm² -2.5mm² , thickness : 6mm , height:65mm , color : grey , mounting type : TH35-7.5、 TH35-15

Product parameter

| Parameter | Data |
|---------------------------------------|--------------------|
| Packing unit (PCS) | / |
| NW per piece(g) | / |
| Layers | 1 |
| Number of connections | 3 |
| Rated cross section(mm ²) | 2.5 |
| Color | grey |
| Insulation material | PA |
| Flame retardant grade (UL94) | V0 |
| Rated voltage(V) | / |
| Rated current(A) | / |
| Temperature of insulation material | -40 ~ +125 |
| Wire feed | Above the terminal |

Product certification

| Parameter | Data |
|--------------------|-------------|
| Certification logo | CE |
| Certification logo | RoHS |

Technical data

| Parameter | Data |
|---|------------------------|
| Connection Method | Spring-cage connection |
| Stripping length(mm) | 8 |
| Solid conductors(mm ²) | 0.2-2.5 |
| Solid conductors AWG | / |
| Stranded conductors(mm ²) | 0.2-2.5 |
| Stranded conductors AWG | / |
| Operating temperature () | -40 ~ +105 |
| Ambient temperature (storage/transportation) () | -25 ~ +60 |
| Relative humidity | 30% ~ 90% |
| Connection in acc. with standard | IEC 60947-7-1 |

Dimension

| Parameter | Data |
|---------------|------|
| Width(mm) | 74 |
| Thickness(mm) | 6 |
| Height(mm) | 65 |