


## HIGH EFFICIENCY RECTIFIER

### FEATURES

- Low cost construction
- Fast switching for high efficiency.
- Low reverse leakage
- High forward surge current capability
- High temperature soldering guaranteed:  
260°C/10 secods/.375"(9.5mm)lead length at 5 lbs(2.3kg) tension

### MECHANICAL DATA

- Case: Transfer molded plastic
- Epoxy: UL94V-O rate flame retardant
- Polarity: Color band denotes cathode end
- Lead: Plated axial lead, solderable per MIL-STD-202E method 208C
- Mounting position: Any
- Weight: 0.042ounce, 1.19 grams



### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25 °C ambient temperature unless otherwise specified Single Phase, half wave, 60Hz, resistive or inductive load For capacitive load derate current by 20%







	SYMBOLS	HER 301	HER 302	HER 303	HER 304	HER 305	HER 306	HER 307	HER 308	UNITS
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	50	100	200	300	400	600	800	1000	Volts
Maximum RMS Voltage	$V_{RMS}$	35	70	140	210	280	420	560	700	Volts
Maximum DC Blocking Voltage	$V_{DC}$	50	100	200	300	400	600	800	1000	Volts
Maximum Average Forward Rectified Current 0.375"(9.5mm) lead length at $T_A=50^\circ\text{C}$	$I_{(AV)}$	3.0								Amp
Peak Forward Surge Current 8.3mS single half sine wave superimposed on rated load (JEDEC method)	$I_{FSM}$	125								Amps
Maximum Instantaneous Forward Voltage @ 3.0A	$V_F$	1.0		1.3		1.5		1.7		Volts
Maximum DC Reverse Current at Rated DC Blocking Voltage	$I_R$	$T_A = 25^\circ\text{C}$								$\mu\text{A}$
		$T_A = 125^\circ\text{C}$								
Maximum Full Load Recovery Current,full cycle average 0.375"(9.5mm)lead length at $TL=55^\circ\text{C}$	$I_{R(AV)}$	150								$\mu\text{A}$
Maximum Reverse Recovery Time(NOTE 1)	$t_{rr}$	50				75				ns
Typical Thermal Resistance (NOTE 2)	$C_J$	70				50				PF
Typical Thermal Resistance(NOTE 3)	$R_{\theta JA}$	20								$^\circ\text{C}/\text{W}$
Operating Junction Temperature Range	$T_J, T_{STG}$	(-55 to +150)								$^\circ\text{C}$

#### Notes:

1. Test Condition:  $I_F=0.5\text{A}$ ,  $I_R=1.0\text{A}$ ,  $I_{RR}=0.25\text{A}$
2. Measured at 1.0 MHz and applied reverse of 4.0 V
3. Thermal resistance from junction to ambient with .375"(9.5mm)lead length, P.C.B. mounted. .

## HIGH EFFICIENCY RECTIFIER

### RATING AND CHARACTERISTIC CURVES HER301 - HER308



#### Disclaimer

All product, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.