


Push-in terminal block-UJ6-16 - 421514



Push-in terminal block , rated voltage : 1000V , Max. operating current : 76A , connection method : spring connection , number of connections : 2 , crimping range : 1.5mm<sup>2</sup> -25 mm<sup>2</sup> , AWG : 16-4 , thickness:12.2mm , height:50.6mm , color : grey , mounting type : TH35-7.5、 TH35-15

## Product parameter

Parameter	Data
Packing unit (PCS)	30
NW per piece(g)	35.1
Layers	1
Number of connections	2
Rated cross section(mm <sup>2</sup> )	16
Color	grey
Insulation material	PA
Flame retardant grade	V0
Temperature of insulation material	-40 ~ +125
Wire feed	Above the terminal

## Product certification

Parameter	Data
Certification logo	
Certification logo	
Certification logo	

## Technical data

Parameter	Data
Connection Method	Spring connection
Stripping length(mm)	22
Solid conductors(mm <sup>2</sup> )	1.5-25
Solid conductors AWG	16-4
Stranded conductors(mm <sup>2</sup> )	1.5-16
Stranded conductors AWG	16-6
Connection in acc. with standard	IEC 60947-7-1
Operating temperature ( )	-40 ~ +105
Ambient temperature (storage/transportation) ( )	-25 ~ +55
Relative humidity	30% ~ 90%

## Dimension

Parameter	Data
Width(mm)	74
Thickness(mm)	12.2
Height(mm)	50.6

## Business data

Parameter	Data
End cover -UJ6-16G - 422122-Packing unit (PCS)	50
End cover -UJ6-16G - 422122-NW per piece(g)	4.4
End cover -UJ6-16G - 422122-Width(mm)	74
End cover- UJ6-16G - 422122-Thickness(mm)	2.2
End cover- UJ6-16G - 422122-Height(mm)	43.5