

Push-in terminal block - UJ6-2.5JD/3L - 421754





Push-in terminal block, connection method : spring connection , number of connections : 7 , crimping range : 0.2mm² -4mm² , AWG : 24-12 , thickness:5.2mm , height: 35.2mm , color : grey , mounting type : TH35-7.5、 TH35-15

Product parameter

Parameter	Data
Packing unit (PCS)	/
NW per piece(g)	29.1
Layers	4
Number of connections	7
Rated cross section(mm ²)	2.5
Color	grey
Insulation material	PA
Flame retardant grade	V0
Temperature of insulation material	-40 ~ +125
Wire feed	Above the terminal

Product certification

Parameter	Data
Certification logo	
Certification logo	

Technical data

Parameter	Data
Connection Method	Spring connection
Stripping length(mm)	11
Solid conductors(mm ²)	0.2-4
Solid conductors AWG	24-12
Stranded conductors(mm ²)	0.2-2.5
Stranded conductors AWG	24-14
Connection in acc. with standard	IEC 60947-7-1
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +55
Relative humidity	30% ~ 90%

Dimension

Parameter	Data
Width(mm)	99.5
Thickness(mm)	5.2
Height(mm)	91.1

Business data

Parameter	Data
End cover -UJ6-2.5JD/3LG - 422159-Packing unit (PCS)	/
End cover -UJ6-2.5JD/3LG - 422159-NW per piece(g)	7.8
End cover -UJ6-2.5JD/3LG - 422159-Width(mm)	99.4
End cover- UJ6-2.5JD/3LG - 422159-Thickness(mm)	2.2
End cover- UJ6-2.5JD/3LG - 422159-Height(mm)	87.8